






Absolute Type Filter Mounting Frames

The Email mounting frame system has been designed for use in single or multiple absolute type filter installations.

Each 14 gauge zinc-dichromate plated mild steel frame is precision pierced to permit rapid on-site installation with 3/16" diameter solid rivets. Before riveting, all sides of the mounting in contact with other frames or duct housings should be coated with a suitable mastic sealant.

When installed, the side of the mounting frame with double alignment strips should be in the downward position so that the filter will bear evenly against the inside flange.

Each mounting frame is supplied with four removable clamp assemblies which are attached to each inner corner of the mounting frame. Each clamp assembly comprises a clamp arm, screw and spring. This assembly provides a constant pressure against the filter gasket after the filter is installed and clamp screw the adjusted.



This constant pressure compensates for any set or deformation the gasket may experience after initial installation and ensures a constant seal at all times.

To suit filter size	Mounting frames	Overall depth	Part No.	
(mm)	(mm)	(mm)		_
305 x 305 x 149	327 x 327 x 152	267	1589-0010/303	
610 x 610 x 149	632 x 632 x 152	267	1589-0010/304	
610 x 610 x 292	632 x 632 x 203	406	1589-0010/305	
610 x 762 x 292	632 x 784 x 203	406	1589-0010/306	
610 x 762 x 149	632 x 784 x 152	267	1589-0010/307	
610 x 1219 x 149	632 x 1241 x 152	267	1589-0010/309	
AES E	nvironn	nentai		

Sydney: Address: Email: Tel 1300 550 116 Fax 1300 550 117 19 Saggartfield Road Minto NSW 2566 sales@aesenvironmental.com.au www.aesenvironmental.com.au



© 2011 AES Environmental (SA) Pty Ltd

National Tel. Hotline 1300 550 116

Bulletin no. 8A.11.05AES103 REV2

ABN 74 136 515 430