

Service Pleats

The Service Pleat is a replaceable pleated media cartridge that fits standard "U" channel holding frames. The element is manufactured from the same non-woven reinforced cotton/synthetic media as the Interfold panel filters.

Air Filtering systems may now be economically upgraded to a medium efficiency filter while still utilising existing pad holding frames.

The Service Pleat installs in seconds without special loading tools or the requirement of special clips on gate assemblies. Service Pleats seals top and bottom with an average of filter media and "friction" fits at the inner edge of the holding frame eliminating air bypass.

Service Pleats provide greater efficiency and longer service life than conventional flat panel filters, with service contracts being an excellent application for use.

Service Pleats are available in nominal 50mm in E-Pleat media with average efficiencies of 30%, and Ultrapleat media with clean efficiency of 20%+. 100mm depths and custom sizes are also made to order.



Low operating cost:
excellent dust holding capacity results in long duty cycle.



Easy mounting:
Service pleats can be installed into existing holding frames in seconds




Single plane sealing:
maintenance personnel can visually check the seal between the filter and the holding frame.


AES Environmental

Service Pleats


Installation Instructions



1. Compress element and place diagonally in holding frame. Rotate element into centre of frame with edges under entering air lip of frame.



2. Grasp the three outer most pleats on one side of the element and pull to the inner edge of the frame. Repeat process on opposite side.



3. Compress the two outer most pleats of the element into the inner edges of the frame. Space remaining individual pleats evenly along the face of the frame for best results.

Type	Nominal Size	Standard Pleat Part No.
30% AVERAGE EFFICIENCY	305x610x50	IFSGP50-305610
	406x508x50	IFSGP50-406508
	406x635x50	IFSGP50-406635
	508x508x50	IFSGP50-508508
	508x610x50	IFSGP50-508610
	610x610x50	IFSGP50-610610
	508x635x50	IFSGP50-508635
20%+ CLEAN EFFICIENCY	305x610x50	IFSFP50-305610
	406x508x50	IFSFP50-406508
	406x635x50	IFSFP50-406635
	508x508x50	IFSFP50-508508
	508x610x50	IFSFP50-508610
	610x610x50	IFSFP50-610610
	508x635x50	IFSFP50-508635

Other media sizes also available - for further information please contact your nearest Email Air Handling sales branch

Addresses

Sydney: Tel 1300 550 116 Fax 1300 550 117

Address: 19 Saggartfield Road Minto NSW 2566 Email: sales@aesenvironmental.com.au

National Tel. Hotline 1300 550 116

National Fax 1300 550 117

© 2011 AES Environmental
AESE



www.aesenvironmental.com.au

