



Water Mist Eliminator

Applications

The Email Air Handling Water Mist Eliminator effectively removes water or oil mist, fog and droplets from new or recirculated airflow. Designed for use in applications requiring air to be free of condensation, such as electrical equipment areas and transmitter stations. Can also be used in conjunction with steam or mist type humidifiers, or in HVAC systems with air or chilled water coils.

Construction

The 2 inch deep media pack consists of multiple alternate layers of crimped and flat woven screen. It is encased in a rigid, 4 inch deep enclosing frame, designed to prevent any air by-pass. An all stainless-steel construction ensures that the Water Mist Eliminator is fully protected against corrosion.

Installation /Maintenance

The Email Air Handling Water Mist Eliminator must be installed vertically to ensure peak operational efficiency. A 'TOP' label is included on the unit for proper orientation when installing. As water is channelled through the bottom of the unit, mounting hardware needs to be designed accordingly with adequate drainage.

Mounting frames can be easily bolted or riveted together to form banks, with larger banks requiring welded diagonal support beams for added support.

How to specify

Mist Eliminators shall be Email Air Handling type Water Mist Eliminator. They shall be a fixed, cleanable all metal panel type. Each Mist Eliminator shall consist of stainless steel screen media and enclosing frame. Media pack shall be constructed of corrugated and flat layers of stainless steel wire. Depth of media pack shall be 2 inches. Enclosing frame shall be stainless-steel construction 100mm deep with reinforced corners.

Made in Australia

Part Number	Description	Face dimensions	Optimim Face Velocity	Pressure Drop
1516-3570/1	Water Mist Eliminator Cell	610 x 610 mm	500 fpm	26 Pa
1516-3580/1	Mounting frame to suit			

Addresses

Sydney: Tel 1300 550 116 Fax 1300 550 117

Address: 19 Saggartfield Road Minto NSW 2566 Email: Sales@aesenvironmental.com.au



www.aesenvironmental.com.au

National Tel. Hotline 1300 550 116

National Fax 1300 550 117



© 2011 AES Environmental
AESE